

UnderwaterFishLight.com Portable HID Fishing Light Operation Instructions

Congratulations on your purchase of one of the world's finest portable fish attracting systems!

Contents: Waterproof Container, Control box mounted to lid of container, 9' cord with attached GFCI plug, 50' /100' underwater UL approved wire, Sealed 175 watt mercury vapor light assembly with attached bulb protector and weight, Velcro Strap.

Instructions: In order to use this system, you must have available a generator (with a GFCI outlet) or an **approved 1000 watt inverter** (with a GFCI outlet) hardwired to a 12 volt battery.

1. Remove lid and place on a flat surface.
2. Remove Light assembly and lower into water.
3. Use the included Velcro strap to secure the wire to a cleat/handrail once desired depth of light is in place below the surface.
4. Plug in the GFCI plug into a GFCI outlet of either a Generator or 1000 watt inverter. The light will then turn on.
5. To turn off the light while still in the water, you can simply push the Test button located on the GFCI plug.
6. To turn the light on push the Reset button located on the GFCI plug.

Notes: *(please read carefully)*

The light will turn on automatically when first plugged in.

Because this is a fully sealed unit, the control box will heat up over time.

It is **not recommended** to run the light consecutively for more than **4 hours at a time**.

If you would like to run the unit longer, a 30 minute cool down period is recommended.

The amount of heat produced will vary on the ambient air temperature, so **periodically check the control box** and make sure it doesn't overheat. It is also **not recommended** to have the light turned on out of the water for more than 10 minutes. The bulb will heat up the sealant around the bulb and cause the seal to fail.

Storage: Rinse off all of the components (**with the exception of the GFCI plug**) with fresh water after each use. Place all of the components back into the container after they dry. Close the lid and store the unit.

If you have questions or assistance in setting up the unit, Please call (941-697-3501)

Warning: **If for any reason your system should cease to function, unplug the unit immediately as a safety precaution then call (941) 697-3501.** If you have the unit plugged in to a properly working GFI there should be no problems, but just to be sure, unplug the unit if the bulb is not functioning properly.

1 YEAR WARRANTY: This unit will be covered for 1 year (to the original purchaser with receipt) from the date of purchase for any manufacture defects. Any Defective part(s) will be replaced or repaired FREE of charge. The purchaser Will/Must make arrangements to ship/transport the unit to the Manufacturer. This does not cover bulb breakage or any damage to the unit by boat, prop, fishing hooks etc.. Or if the unit has been tampered with or misused in any way. If the unit/bulb or wire(s) needs to be repaired/replaced from DAMAGE not covered by warranty, the purchaser shall contact the manufacturer (941-697-3501) and request a price quote for the repair.

Disclaimer: The Manufacturer/Designer/Seller of this product is not responsible for any Injury/Death or Damage to property caused by the use of this product. Take any and all safety precautions when using this product. This must be plugged into a UL APPROVED GFI OUTLET. The purchaser agrees to the above by purchasing this unit.